A2D2 LiFePO4

LiFePO4 (Lithium Iron Phosphate Battery)

25.6V / 100Ah (2560Wh)


LFA2-24V100C10-M8B2

CHARACTERISTICS


BATTERY SPECIFICATIONS	
Battery type-Chemistry	LiFePO4
Nominal Voltage	25.6 V
Nominal Capacity	100 Ah
Output Power	2560 Wh
Dimensions (L x W x H)	483 x 170 x 240 mm
Weight	17.9 kg
Terminal Type	M8
Case Material	ABS
Internal Resistance	<20 mΩ
BMS built-in	Yes
Self Discharge per Month	<3 %
Cycle Life	6000 Cycles (0.2 C, 25°C, 100% DOD)
Discharge Temperature	(-20 to 60) °C
Charge Temperature	(0 to 45) °C
Storage Temperature	(0 to 35) °C
Bluetooth	Yes
LCD Screen	No
Connector	No
Heating Function	No
IP Rating	IP65
Voltage Window	21.6-29.2 V
Recommended Charge Voltage	29.2V ±0.20V
Max Charge Voltage	29.2V ±0.20V
Recommended Charge Current	20 A
Max Continuous Charge Current	50 A
Recommended Discharge voltage	22.4V ±0.20V
Max Discharging Voltage	20V ±0.20V
Max Continuous Discharge Current	100 A
Peak Discharge Current	180 A (5±3S)
The maximum number of battery packs supported in series	≤2PCS
The maximum number of battery packs supported in parallel	supported

DIMENSIONS







DISCHARGE CHARACTERISTICS (25°C)




TEMPERATURE EFFECTS ON DISCHARGE (0.5C)



SELF DISCHARGE CHARACTERISTICS



CHARGE CHARACTERISTICS (25°C)



Copyright © www.a2d2.cz